

DYNAMIC CHARACTERISTICS OF INDUSTRIAL ROBOTS,
USING SEGMENTED TRAJECTORIES

الخصائص الديناميكية لمنظومات الذراع الآلي الصناعية
ذات المسارات المجرأة

F.F.G. AREED

Control & Computers dept., Faculty of Engin., El-Mansoura Univ.

ملخص البحث

تمثل منظومات الذراع الآلي الصناعية واحدا من أهم التطبيقات المتقدمة في مجالات التحكم الآلي وهذه المنظومات ذات خصائص ديناميكية شديدة التعذب بسبب توالر اللاخطيات في أجزاء المنظومة . ولذلك فإن السبب التحكم التلقائية لا تصلح للتعامل مع أمثال هذه المنظومات . وفي هذا البحث تمت دراسة للخواص الديناميكية لهذه المنظومات بهدف الحصول على نموذج رياضي ثم تم الحرائق مسار مستمر مناسب يتم تحديده مسبقا تختل فيه ظاهرة التعذب ومن هذا المسار يتم استخراج التزم اللازم لتحريك الذراع . وفي بعض الأجزاء تكون هناك حاجة لاستخدام مسارات مجرأة مثل عمليات اللحام الكهربائي وقد تم الحرائق مسارات مجرأة لمنظومة ذراع آلي ذات ثلاثية الأزرع واستحتاج التزم اللازم لكل ذراع وذلك باستخدام المناخاة على الحاسب الآلي . والبحث يمتوى على دراسة مقارنة بين المنظومة في حالة المسارات المستمرة والمسارات المجرأة .

ABSTRACT

Robotic systems represent one of the most advanced industrial applications. Such robotic systems have a severe oscillatory behaviour, thus the conventional control techniques are not suitable to deal with it . In the present paper, the dynamic behaviour of robotic systems is studied and a dynamic model for such systems is obtained. A suitable trajectory for each link is pre-determined. The technique introduced proposes a segmented trajectory rather than a continuous one . A comparative study between the behaviour of the system with the proposed technique and that proposed in [7] is introduced .

The above mentioned algorithm assumed that the chosen path is continuous and this can be used in some tasks, required to be carried-out by the robot. But in other tasks, it is sometimes required that the robot must move a short distance from a point to another neighbouring point i.e., the path is not continuous but, it is a segmented path. Such paths are required in different tasks, such paths are welding, paint spraying, carrying a tray of drink,.....etc.

DYNAMICS USING SEGMENTED TRAJECTORIES

The technique used for dividing the previous continuous trajectories into segmented trajectories can be explained as follows:

The base line is divided into equal intervals Δt . In our case Δt is chosen to be 0.1 sec.

Fig. (9), (a), (b), (c) illustrates the desired segmented trajectories for the three links (1), (2) & (3) respectively. The figure shows the desired joint paths for a typical motion by straight lines approximation-(incremental and decremental steps).

Each segment on the trajectory has a beginning and final condition. The final condition of the first segment is the beginning condition of second segment and so-on, e.g.:

For the first segment:-

$$\begin{aligned} \text{at } t=0, & \quad \theta_1(0) = 0, \quad \theta_2(0) = 0.1, \quad \theta_3(0) = 0.2 \\ \text{at } t=0.1, & \quad \theta_1(t) = 0.01, \quad \theta_2(t) = 0.1, \quad \theta_3(t) = 0.2 \end{aligned}$$

For the second segment:-

$$\begin{aligned} \text{at } t=0.1, & \quad \theta_1(0) = 0.1, \quad \theta_2(0) = 0.1, \quad \theta_3(0) = 0.2 \\ \text{at } t=0.2, & \quad \theta_1(t) = 0.06, \quad \theta_2(t) = 0.12, \quad \theta_3(t) = 0.22 \end{aligned}$$

For the third segment:-

$$\begin{aligned} \text{at } t=0.2, & \quad \theta_1(0) = 0.06, \quad \theta_2(0) = 0.12, \quad \theta_3(0) = 0.22 \\ \text{at } t=0.3, & \quad \theta_1(t) = 0.17, \quad \theta_2(t) = 0.17, \quad \theta_3(0) = 0.25 \dots\dots\dots\text{etc.,} \end{aligned}$$

The angular velocities of links (1), (2) & (3) respectively, using these segmented paths are shown in Fig. (10), (a), (b) & (c). The applied torques to links (1), (2) & (3) are shown in Fig. (11), (a), (b) & (c) respectively.

COMPARATIVE ANALYSIS:-

Comparing Fig. (8), (a), (b) & (c) with Fig. (11) (a), (b) & (c) it is clear that the torques produced by the actuators, in case of segmented trajectories have much regular change, than those torques obtained in case of continuous trajectories. The torques produced in case of continuous trajectories have an oscillatory behaviour. Thus, the torques shown in Fig. (11), ((a), (b) & (c)) are much suitable for stable operation. In addition, it is clear that the motors producing these torques reach steady-state faster than those producing the torques shown in Fig. (8), ((a), (b) & (c)).

CONCLUSIONS:-

In the present paper a suggested technique for assuming a segmented robot trajectory is introduced. The proposed segmented trajectory as illustrated acquired a torque with stable behaviour. The segmented trajectory of a robot is required in special fields of industry such as spot and arc welding.

REFERENCES:-

- 1- D.E.Orin et al, (1979) :Kinematic and Kinetic analysis of open chain Linkages Utilizing Newton-Euler methods, Math. Bi osc. Vol.43, PP107-130.
- 2- M.A.Hashish & others, (1985) Bilinearization in robotic simulation, IBM tec. report O13, Cairo.
- 3- R.P.Paul, (1981): Robot manipulators: Mathematics, programming & control, MIT press, Cambridge.
- 4- M.Renaud, (1983): An efficient iterative analytical procedure for obtaining a robot manipulator dynamic model, 1 st Int-Symp. of robotic research, Betton woods, U.S.A.
- 5- S.Megahed, (1981) New Lagrangian Formulation of manipulator dynamics, 11 th I.S.I.R. Tokyo.
- 6- W.E.Synder, (1985): Industrial robots: Computer interfacing and control, prentice-Hall, Inc., Englewood Cliffs, Newjersey.
- 7- F.F.G.Areed & others, (1988): A new suggested numerical control technique for nonlinear robotic systems, 2 nd Int. Workshop on methodologies and Application of complex system theory, Cairo, PP.294-306.






Figure (1)




(A)




(B)


Figure (2)



(A)




(A)




(B)

Figure (3)




(B)


Figure (4)



(A)




(A)



(B)

Figure (5)



(B)

Figure (6)





Figure (7)






Figure (8)




Figure (9)









Figure (10)



(A)



(B)



(C)

Figure (11)